

Maintenanc kit - oxidative oiled parquet

THE MAINTENANCE KIT CONSISTS OF:

1 liter Natural Soap | 250 ml Oil Refresher | 100ml Monocoat oil

NATURAL SOAP is a purpose-made quality soap, which due to its nourishing properties quickly closes the pores of the wood and protects against dirt and penetration of liquids.

OIL REFRESHER may be used for all oiled surfaces and is especially suitable for the yearly maintenance of wood surfaces.

Available in Natural and White.



1. TAKE SOME PRECAUTIONS

1. Clean the floor regularly with a vacuum cleaner or soft broom; particles of dirt and grit that are left behind can damage the surface of the floor.
2. Remove stains immediately with a well-wrung cloth. Worn-in stains are difficult to remove.
3. Never use too much water when mopping; instead use a well-wrung floor cloth.
4. Never clean the floor with pure water; always use a product for the maintenance of oiled parquet.
5. Do not use traditional cleaning products.
6. Place doormats at exterior doors.
7. Place beige, felt floor protectors under chair and table legs; do not use coloured floor protectors!
8. Avoid wearing damaged or worn stiletto heels.
9. Place a protective mat under chairs with wheels.
10. Place a protective dish under flowerpots.
11. Do not drag heavy objects across the floor; lift them up to avoid scratches.
12. Be careful with open windows - a rain shower can damage the floor.

2. FIRST TREATMENT AFTER INSTALLATION

After installation we advise a first cleaning with Woca Oil Refresher.

1. Shake the container carefully. The floor must be free from dust before treatment.
2. Clean the floor with 125 ml Oil Refresher mixed into 5 liter of cold water.
3. Treat with a light wrung floor cloth or mop lengthwise of the floor. Immediately afterwards, dip floor cloth or mop into mixture and wipe the floor with hard wrung floor cloth or mop again lengthwise of the wood.
4. Leave the floor to dry for approx 2 hours before use.

14 days later you can start the maintenance with the Natural Soap.



Maintenanc kit - oxidative oiled parquet

3. REGULAR CLEANING WITH NATURAL SOAP

Natural Soap is ideal for the cleaning and maintenance of all oiled, UV oiled or soaped wood surfaces.

1. Shake the Natural Soap carefully before use.
2. 125 ml Natural Soap is mixed into 5 liter of cold water.
3. Always mop the floor with soap water on hard-wrung mop or cloth in order to reestablish the protective Natural soap film.
4. Leave the floor to dry for approx 5-10 minutes before use.



4. ANNUAL CLEANING WITH OIL REFRESHER

This Oil Refresher combines efficient cleaning with re-oiling as addition oil is penetrating into the wood of the floor forming a mat protective layer in the surface. Oiled floors should be regularly maintained – normally once a year, but more often when it comes to floors exposed to extremely hard wear. Follow the instructions from point 2.

5. RESTORATION WITH RUBIO MONOCOAT OIL PLUS

This treatment is recommended where scratches or burn marks are present, or where heavy wear is showing either in patches or large areas of the floor. Ask for professional advice before starting.

SCRATCHES AND BURN MARKS:

1. Lightly sand the spot to be restored.
2. Eliminate dust.
3. Apply Rubio Monocoat Oil Plus with a cloth or sponge.
4. After a few minutes, wipe away any surplus product with a cloth or paper towel.
5. The surface can be used again after 24 to 36 hours.

WEAR

1. Apply a limited amount of oil to a polishing pad (kitchen paper or a dry cotton cloth, if necessary).
2. Evenly distribute the oil by rubbing in the direction of the wood grain until just beyond the edge of the worn area in order avoid visible edge marks.
3. Remove the excess oil immediately with kitchen paper.
4. Allow to dry for 24-36 hours.

