



## DECLARATION OF PERFORMANCE

|                                              |                                                                                                                              |
|----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| <b>Reference</b>                             | Cottage-19                                                                                                                   |
| <b>Commercial name</b>                       | Cottage                                                                                                                      |
| <b>Product type</b>                          | Engineered wood flooring – 3-layer<br>190 x 630-1860 x 14 (3) mm                                                             |
| <b>CE standard</b>                           | EN14342 : 2013 + A1                                                                                                          |
| <b>Application</b>                           | Interior floor covering – according to the manufacturer's specifications and national normative rules – floated installation |
| <b>Certification number</b>                  | 1393-CPD-0870                                                                                                                |
| <b>System of assessment and verification</b> | System 3                                                                                                                     |
| <b>Manufacturer</b>                          | Lamett Europe<br>Ter Donkt 2<br>8540 Deerlijk<br>Belgium                                                                     |
| <b>Harmonised standard</b>                   | Timber Research and Development Institute Praha – NB 1393                                                                    |

| Essential characteristics                   | Performance           |
|---------------------------------------------|-----------------------|
| <b>Reaction of fire</b>                     | Dfl-s1                |
| <b>Linked with the minimum mean density</b> | 650 kg/m <sup>3</sup> |
| <b>And minimum overall thickness</b>        | 14 mm                 |
| <b>Formaldehyde emission</b>                | E1                    |
| <b>Pentachlorophenol content</b>            | ≤ 5 ppm               |
| <b>Slipperiness</b>                         | -                     |
| <b>Thermal conductivity</b>                 | 0.14 W/mK             |
| <b>Biological durability</b>                | Class 1               |

Bruno Descamps  
CEO Lamett Europe NV