

technical data sheet

EN

Product specifications

Multi-Ply Oak wood flooring	EN 14342 (Free Class)	DOP PQ2022-7
Dimensions	Plank	600 x 120 x 14/ 3 mm
	Box	20 planks / 1,44 m ² / 11 kg
	Nested lengths	-
	Pallet	96 boxes / 1129,96 m ² / 1080kg
Density	EN ISO 23996	+/- 650 kg/m ³
Installation	ISO 24334	T&G (glued)
Top layer		3 mm European oak (Quercus Robur)
Grading		Rustic B
Surface		Slightly brushed
Bevel		Bevel 4V
Gloss level	60°	10-15%
Finishing		Oxidative oil
Warranty conditions	Residential use Commercial use	20 years upon request
Application	EN 14342	Class 23



Producteigenschappen

Property	Test method	min. req.	result
Indoor air certifications			A, REACH
Fire resistance	 EN 13501-1		Dfl-S1
Slip resistance	 EN 13893		DS (≥ 0.30)
Formaldehyde emission	 EN 717-1	≤ 0.124 mg/m ³	E1
Pentachlorofenol content	 EN 12673	< 5 ppm	< detectable limit
Underfloor heating	 EN 12667	R < 0.15 m ² K/W	R = 0,12 m ² K/W OK (max +28°C) + glued
Biological durability			Class 1

Cleaning and maintenance instructions: www.lamett.eu

