Connect 8 V4.
Technical data.

BERRY ALLOC

03/2023

	contains	m²	ft²	weight
1 pack Connect 8 V4	9 planks	2,20 m²	23.71 ft²	15,7 kg
1 pallet Connect 8 V4	56 packs	123,34 m²	1327.61 ft²	891 kg

product specifications

Dimensions	1288 x 190 mm
Total thickness	8 mm
Bevels	4
Loc System	DuoLoc
Level of use according to European standard EN10874	23 heavy domestic use
	32 general commercial use
Residential warranty	lifetime
Commercial warranty	5 years

Warranty conditions on www.berryalloc.com.

composition

Surface layer	Direct laminated paper, impregnated with melamine resin.
Substrate	Moisture resistant High Density Fiberboard (HDF).
Backing	Direct laminated paper, impregnated with melamine resin.

test results

Abrasion resistance	EN13329	AC4 (IP≥4000)
Impact resistance	EN13329	small ball : ≥ 35 mm - big ball : ≥ 750 mm
Thickness swelling	ISO24336	12% (requirement ≤ 18%)
Fire resistance	EN13501-1	Cfl-S1
Formaldehyde emission	EN717-1	E1
Slip resistance	EN13893	DS
Density	EN323	900 kg/m³
Resistance to staining	EN438	5 (groups 1+2) ; 4 (group 3)
Effect of a furniture leg	EN16581	no damage (foot type 0)
Effect of a castor chair	EN425	no damage with type W wheels
Thermal resistance in combination with underlay Excellence Plus	ISO 8302	0,08 m²K/W – Suitable for floor heating/cooling. Detailed instructions on www.berryalloc.com.

EN 14041
CE | UK CA
23 DOP 170-DPLA23-1 | 23 DOC UK 170-DPLA23-1
Berryalloc NV
Industrielaan 100
8930 Menen, Belgium
NB 1161
Laminate floor covering for use within building
www.berryalloc.com

PEFC Certified
Laminate comes from Sustainably Managed Forests, recycled or controlled sources.
PEFC
PEFC/07-31-229
www.pefc.org

ÉMISSIONS DANS L'AIR INTÉRIEUR*
A+
A+ A B C
*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

23

32

laminate.

www.berryalloc.com

Connect 8 V4.
Technical data.

BERRY ALLOC

03/2023

What is a laminate floor made of?



1. An **overlay** that determines the strength and resistance of your floor
2. A **decor paper** for the design
3. A **high-density fibreboard** (HDF) core
4. A **counterbalance** to stabilise and protect the HDF core

laminate.