

# UNICARE X-MATT



0,75L

## PRODUCT DESCRIPTION

UNICARE X-MATT is a universal maintenance product providing an extra protection layer for all types of MATT floors. UNICARE X-MATT can be used on our matt waterborne finishes (FORTICO, Ecofix & OCULTO), laminate, LVT and UV-oiled floors.

UNICARE X-MATT provides an extra protective film and hides micro-scratches maintaining the original look of the floor. The extra matt protection prevents dirt becoming ingrained.

## TECHNICAL DETAILS

APPEARANCE	MILKY
VISCOSITY	THIN LIQUID
DENSITY	1,05
PH VALUE	8
GLOSS LEVEL	MATT

## PRE-TREATMENT

Before using UNICARE X-MATT, make sure that the varnish coat has hardened for at least 10 days. Ensure that the floor is clean before applying the UNICARE X-MATT. You can clean the floor with Hard Floor Fresh. Apply the UNICARE X-MATT on a dry and grease-free surface.

## INSTRUCTIONS FOR USE

Use the UNICARE X-MATT undiluted. Apply UNICARE X-MATT evenly with a microfiber cloth or a mop in the direction of the wood grain. If necessary, a second layer of UNICARE X-MATT can be applied after 1 hour.



### DRYING TIME

Approx. 1 hour at room temperature.



### COVERAGE

+/- 60-80 m<sup>2</sup>/liter.

## AFTER-TREATMENT

For the regular maintenance of varnished floors and floors treated with UNICARE X-MATT, use Ciranova Hard Floor Fresh. To remove old layers of UNICARE X-MATT, use Ciranova Hard Floor Cleaner.

## PRODUCT INFORMATION

- Shelf life : 18 months in original and unopened bottle.
- Store under frost-free conditions.

## SPECIAL INDICATIONS

After use, clean tools with water.

Do not mix with other cleaning products. Keep out of the reach of children.

Ciranova® products are made for the professional user. The instructions specified in the data sheet are formulated after necessary tests were performed and after years of experience. However, they are drawn to our best knowledge and ability. The user must test the application of the product in the for him applicable conditions. Guarantee can not be derived out the text of this technical description.

### PRODUCED BY DEBAL COATINGS NV

Industrieweg 29 – B 8800 Beveren-Roeselare  
tel +32 (0) 51 30 11 40 fax +32 (0) 51 31 26 48  
www.ciranova.be ciranova@ciranova.be